

**MODULA LED LIGHTING SYSTEM**



<b>Module Dimensions:</b>	140.0mm x 22.0mm
<b>Operating Voltage:</b>	Stabilised 24V DC ± 5%
<b>High Output + Emergency PCB:</b>	5 Watt with Emergency 0.29W Option
<b>Lens:</b>	Clear or Diffused
<b>Colour Temperature:</b>	Warm White: 3000 Kelvin Neutral White: 4000 Kelvin
<b>Material:</b>	Antimicrobial Polycarbonate Moulded Lens
<b>Fixings:</b>	M3 Bolt (Stainless Steel 316)
<b>Quality:</b>	British Made: CE Marking: Full Traceability
<b>Ratings:</b>	Module IP 66 : IK 10
<b>Temperature Range:</b>	-30°C to +50°C
<b>Maximum Module Qty.</b>	30 + per Driver
<b>Reverse Battery Protection:</b>	Yes
<b>Luminous Emittance:</b>	75 Lm/w
<b>Emergency Emittance:</b>	253 Lumens



*Feature F48 Modula Rail*

<i>Vandal Resistant</i>	Yes	Tamper Proof screws used
<i>Handrail Diam: 48.3mm x 2mm wall</i>	Yes	Radius face to sit flush in standard handrail
<i>Stainless Steel with PPC Coating</i>	Yes	Available in your RAL Colour
<i>Colour Temperature Options</i>	Yes	3000k, 4000k RGB Etc.
<i>Lux Variable</i>	Yes	All Options available
<i>On/Off – Dimmable System</i>	Yes	Compatible Drivers Provided
<i>Easy Maintenance</i>	Yes	O & M Manual Provided
<i>Easy Installation</i>	Yes	Installation Manual Provided
<i>Quick &amp; Simple Module Replacement</i>	Yes	With Maintenance Instructions
<i>Constant Voltage System</i>	Yes	1 module fails the rest stay on

