



#### Accessory



**Product Family Name:** Canon Spot  
**Product Family Code:** CS->body size<-FL->Beam<->CCT<->Voltage<  
**LED Brand:** Osram  
**LED Colour Temp:** 3000K Warm / 5000K Cool / RGB  
**CRI:** >70  
**Light Source Replaceable:** Yes  
**Power Supply:** LV-Separate or Mains - Intergrated optional  
**Optical Type:** Spot 20° & 30°  
**Optical Distribution:** Single Spot  
**Optical Cover/Lens:** PMMA  
**Dimmable:** n/a (Set by driver for LV version)

**Photocell:** n/a

**Power Cable:** LV = 2m HO5RN-F 2x1mm<sup>2</sup>, Mains = 2m HO5RN-F 3x1mm<sup>2</sup>, RGB = 2m HO5RN-F 5x0.5mm<sup>2</sup>  
**IP Rating:** IP65  
**Mounting:** Stirrup bracket with aiming

**Input Voltage:** LV = 24vDC / Mains = 240vAC

**Control Signal:** n/a (Set by driver for LV version)  
**Chassis Material:** Powder Coated Die-cast Aluminium  
**Chassis Colour:** Grey  
**Optical Cover/lens:** 4mm Tempered Glass  
**Options:** n/a  
**Mechanical Accessories:** Stirrup bracket included  
**Weight (Kg):** 0.95 / 1.95 / 2.1

**System Power (w):** 6w / 13.5w / 18w

**Luminous flux Cool White (lm):** 466 / 889 / 1641  
**Luminous flux Warm White (lm):** 383 / 680 / 1183

**Working Temp:** -20° to +40°C