



'Dinky – Sign Light'



Size illustration



Features

- Compact design
- Lowest Capital Cost
- Philips LED

Product Family Name:	Dinky Sign Light
Product Family Code:	SASIG.>LM Package<
LED Brand:	Philips Lumileds
LED Colour Temp:	4000K or 5000K
CRI:	>70
Light Source Replaceable:	YES
Power Supply:	Integrated (external optional)
Optical Type:	direct
Optical Distribution:	Multi Layer
Optical Cover/Lens:	Yes
Dimmable:	OPTIONAL
Photocell:	OPTIONAL
Power Cable:	Supplied with 6m
IP Rating:	IP65
Mounting:	Pos top 76mm (other sizes available)
Aiming Angles:	NA
UMSUG Codes:	Available soon

Input Voltage:	90-277V
Input Frequency:	50-60Hz
Control Signal:	OPTIONAL
Chassis Material:	Die-cast Aluminium
Chassis Colour:	Two tone Grey
Optical Cover/lens:	Polycarbonate
Mechanical Accessories:	Post top bracket
Weight:	1.6Kg
System Power:	9w, 14w, 18w
Luminous flux:	890LM, 1271LM, 1880LM
LED Luminaire efficacy:	105 Lm/W
Surge Protection	10KV/10KA (20KV/10KA Optional)
Working Temp:	-20° to +50°C
Lifetime:	L90 B50 F10



Model	Lumen Package (LM) 5000K	Lumen Package (LM) 4000K	Power (W)
SA.SL.S1	940	890	9
SA.SL.S2	1343	1271	14
SA.SL.S3	1880	1780	18

Dimensions (mm)

