



## 'Dinky – Sign Light'



Size illustration



<b>Product Family Name:</b>	Dinky Sign Light
<b>Product Family Code:</b>	SASIG.>LM Package<>Post top or Side Entry<
<b>LED Brand:</b>	Philips Lumileds
<b>LED Colour Temp:</b>	4000K or 5000K
<b>CRI:</b>	>70
<b>Light Source Replaceable:</b>	YES
<b>Power Supply:</b>	Integrated (external optional)
<b>Optical Type:</b>	direct
<b>Optical Distribution:</b>	Multi Layer
<b>Optical Cover/Lens:</b>	Yes
<b>Dimmable:</b>	OPTIONAL
<b>Photocell:</b>	OPTIONAL
<b>Power Cable:</b>	Supplied with 6m
<b>IP Rating:</b>	IP65
<b>Mounting:</b>	Post top 76mm (other sizes available) or side Entry 34mm
<b>Aiming Angles:</b>	NA
<b>UMSUG Codes:</b>	Available soon

<b>Input Voltage:</b>	90-277V
<b>Input Frequency:</b>	50-60Hz
<b>Control Signal:</b>	OPTIONAL
<b>Chassis Material:</b>	Die-cast Aluminium
<b>Chassis Colour:</b>	Two tone Grey
<b>Optical Cover/lens:</b>	Polycarbonate
<b>Mechanical Accessories:</b>	Post top bracket
<b>Weight:</b>	1.6Kg
<b>System Power:</b>	9w, 14w, 18w
<b>Luminous flux:</b>	890LM, 1271LM, 1880LM
<b>LED Luminaire efficacy:</b>	105 Lm/W
<b>Surge Protection</b>	10KV/10KA (20KV/10KA Optional)
<b>Working Temp:</b>	-20° to +50°C
<b>Lifetime:</b>	L90 B50 F10

### Features

- Compact design
- Lowest Capital Cost
- Philips LED



Model	Lumen Package (LM) 5000K	Lumen Package (LM) 4000K	Power (W)
SA.SL.S1	940	890	9
SA.SL.S2	1343	1271	14
SA.SL.S3	1880	1780	18

Dimensions (mm)

