



Product Family Name:	Canon 12
Product Family Code:	CAN12-IG->Beam<->LED<->CCT<->Voltage<
LED Brand:	Osram
LED Colour Temp:	3000K Warm / 5000K Cool / RGB
CRI:	>70
Light Source Replaceable:	No
Power Supply:	Separate (Intergrated optional)
Optical Type:	Spot 20° or Asymmetric
Optical Distribution:	Multi Layer
Optical Cover/Lens:	PMMA - One per LED
Dimmable:	n/a
Photocell:	n/a
Power Cable:	0.5m HO5RN-F 3x1mm ²
IP Rating:	IP67
Mounting:	Recessed
Aiming Angles:	n/a

Input Voltage:	24vDC or 240vAC
Control Signal:	n/a
Chassis Material:	Stainless Bezel / Die-cast Aluminium sleeve
Chassis Colour:	Grey
Optical Cover/lens:	8mm Glass - 2274KG rated drive over
Options:	Diffused Anti slip Glass
Mechanical Accessories:	Mounting sleeve included
Weight (Kg):	1.7
Windage (m²):	n/a
System Power (w):	13
Luminous flux:	Warm 783LM, Cool 956LM
LED Luminaire efficacy:	65LM/W
Surge Protection	n/a
Working Temp:	-20° to +40°C
Lifetime:	>50,000hrs