




MainLine LED X



Mounting Brackets

Product Family Name:	Mainline LED X	Input Voltage:	230V
Product Family Code:	MLED-X->colour<->No.LED<->optic<	Control Signal:	Optional DALI & 0-10v
LED Brand:	Cree or Philips	Chassis Material:	Anodised Aluminium
LED Colour Temp:	3000K, 4000k or 5000k or RGB	Chassis Colour:	Natural (Painting optional)
CRI:	>70	Optical Cover/lens material:	Polycarbonate
Light Source Replaceable:	Yes	Mechanical Accessories:	n/a
Power Supply:	On Board	Length:	300mm, 500mm, 600MM, 1000mm & 1220MM
Optical Type:	Individual Optional	System Power:	13w/m, 20w/m, 40w/m
Optical Distribution:	90° Stnd - 6°, 10°, 12°, 19°, 35°, Asymmetric optional	LED Luminaire efficacy:	120Lm/w
Optical Cover/Lens:	Yes	Surge Protection	n/a
Dimmable:	Optional	Working Temp:	-0 to +50°C
Photocell:	n/a	Lifetime:	>50,000hrs
Power Cable:	Optional		B50, L70, F10
IP Rating:	IP65		
Mounting:	Swivel Bracket		
Aiming Angles:	180°		
UMSUG Codes:	No		