



| | |
|----------------------------------|-----------------------------------|
| Product Family Name: | Surface Slimline Linear LED |
| Product Family Code: | ATLNSS..... |
| LED Brand: | Nichia/Lumileds/Osram/Cree/Edison |
| LED Colour Temp: | 3500-6500K |
| CRI: | >70 |
| Light Source Replaceable: | YES (if unpotted) |
| Power Supply: | Separate |
| Optical Type: | 120° |
| Optical Distribution: | Multi Layer |
| Optical Cover/Lens: | Clear |
| Dimmable: | OPTIONAL |
| Photocell: | n/a |
| Power Cable: | 1m |
| IP Rating: | IP20 (IP67 when potted) |
| Mounting: | Recessed |
| Aiming Angles: | n/a |

| | |
|-------------------------|------------------------|
| Input Voltage: | Set by external driver |
| Input Frequency: | Set by external driver |
| Control Signal: | Set by external driver |

| | |
|--------------------------------|------------------------------|
| Chassis Material: | Anodised Aluminium |
| Chassis Colour: | Natural |
| Optical Cover/lens: | (Optional plastic) |
| Mechanical Accessories: | Clips and brackets available |
| Weight: | >1kg per meter |

| | |
|--------------------------------|-----------------|
| System Power: | 7.2 to 43.2w/m |
| Luminous flux: | 480 to 3300Lm/m |
| LED Luminaire efficacy: | 67 to 76Lm/W |
| Surge Protection | n/a |
| Working Temp: | -40° to +50°C |
| Lifetime: | >30,000 |



Installation

