




Optical block



luminaire



| | | | |
|----------------------------------|---|--------------------------------|---|
| Product Family Name: | Terceira Post top luminaire | Input Voltage: | 90-277V |
| Product Family Code: | T2.>Power<.>Colour temp<.>distribution<>LM< | Input Frequency: | 50-60Hz |
| LED Brand: | Philips Lumileds or Bridgelux COB | Control Signal: | OPTIONAL |
| LED Colour Temp: | 3000K, 4000K or 5000K | Chassis Material: | Die-cast Aluminium |
| CRI: | >70 | Chassis Colour: | Black |
| Light Source Replaceable: | YES | Optical Cover/lens: | Polycarbonate |
| Power Supply: | Intergrated | Mechanical Accessories: | N/A |
| Optical Type: | Road Type I, II, III, IV & Area Type V (360°) | Weight (kg): | 9 |
| Optical Distribution: | Multi Layer | System Power (w): | 360° - 20 / 40 / 50w, Road Optic - 28 / 53w |
| Optical Cover/Lens: | N/A | Luminous flux: | 1500LM to 5300LM |
| Dimmable: | OPTIONAL | LED Luminaire efficacy: | 100 Lm/W |
| Photocell: | OPTIONAL | Surge Protection | 10KV/10KA (20KV/10KA Optional) |
| Power Cable: | OPTIONAL | Working Temp: | -20° to +50°C |
| IP Rating: | IP65 | Lifetime: | L90 B50 F10 |
| Mounting: | Post top 60-76mm | | |
| Aiming Angles: | na | | |



Ark Lighting Ltd
McGann House
Chesham Rd
Barnsley
South Yorkshire
S70 2NT, UK
t: 01226 320737
e: sales@arklighting.co
www.arklighting.co

