


## CW



Attractive modern design general purpose surface mounted lighting system available with a wide variety of light source options and ideal for domestic or commercial applications. Base, diffuser and eyelid are manufactured using anti-corrosive high impact injection moulded polycarbonate. Options include opal or clear diffusers, maintained emergency packs, black, white or silver grey colour finish, high pressure sodium and a wide choice of compact fluorescent versions, tamper proof screws and integral photocell options available.





**L.E.D SMD chip**

- S.1 - SON-E (E27) Internal ignitor
- S.2 - SON-T (E27) External ignitor
- CF.1 - Compact Fluorescent L, 2 Pin, (G23)
- CF.6 - Compact Fluorescent TE, 4 Pin, (Gx24q-4)
- CF.7 - Compact Fluorescent OE, 4 Pin, (Gx24q-5)
- CF.8 - 2D, 2 Pin, (GR8)
- CF.9 - 2D, 4 Pin, (GR10q)



DESCRIPTION	LAMP	Wt.(kg)	PART No.
LED -SMD 11w/22w/33w	LED	1.80	CW33LED

\*Supplied with Opal diffuser as standard

**CEILING MOUNTING**



**CEILING MOUNTING IN ISLES**



- PHOTOCELL OPTIONS ARE AVAILABLE ON ALL TYPES, TO ORDER SUFFIX CODE WITH /PC. e.g. CW 70SCL /PC
- SUITABLE FOR CEILING MOUNTING - SEE IMAGE BELOW TO ORDER SUFFIX WITH /CM e.g CW33LED/CM
- SUITABLE FOR CEILING MOUNTING IN ISLES TO ORDER SUFFIX WITH /CMI e.g CW33LED/CMI

**TECHNICAL SPECIFICATION**

HOUSING	Thermo-plastic polycarbonate
DIFFUSERS	Polycarbonate
PHOTOCELL	Photocell available for all types
REFLECTORS	Zinc steel polyester coated
CONTROL GEAR	Available with a wide variety of options
ACCESS	Front opening
FIXINGS	Corrosion and anti-seizure proof
COLOURS	Black RAL 9011, Silver RAL 7000 White RAL 9003

**ACCESSORIES**

3 Hour Emergency Packs available for:  
 28-38W 2D with HF Gear      Suffix/EMG  
 HF Control Gear                      /HF

IP65 CE CL1 Ta 25°C Max Ik10 (20 Joule) shock resistance

