

Canon 30 Uplighter with adjustable beam angle



LUMINAIRE:

- Die-cast aluminum body and aluminum mounting box
- Stainless steel frame
- Shock resistant tempered glass cover
- Walk over and drive over capacity up to 12 mph

OPTICAL SYSTEM:

- Polycarbonate UV-resistant lenses
- Symmetrical light distribution
- Ultra spot, spot, narrow, medium, flood, wide flood and elliptic optics
- Built-in anti-glare grille for improved visual comfort
- Directional optical system $-5^{\circ} \sim +15^{\circ}$


LIGHT COLOUR MANAGEMENT:

- High uniformity and consistency for facade lighting
- RGBW version available for colour mixing versions

INSTALLATION:

- For outdoor installation with ground recessed mounting box
- Anti-slip glass as optional accessory for improved safety (MOQ)







QUICKINFO













Inground 30W, 4 high-power LEDs
 Input DC24V constant voltage
 Remote power supply ordered separately
 On-board driver available on request (240v)

DIMENSIONS








CODE	Optics	Light colour	Control	Finish colour	Luminous flux
CIG1914W30	 spot 5° 0005	 2700K 2780	ON/OFF	 stainless steel 01	2,250lm
	 spot 8° 0008	 3000K 3080			
	 narrow 12° 0012	 4000K 4080			750lm
	 medium 20° 0020				
	 medium 30° 0030				
	 flood 45° 0045				
	 wide flood 60° 0060				
	 elliptic 10°x70° 1070				

Accessories:



honeycomb
for models with optics > 30°



anti-slip glass

Note: MOQ may apply