

Canon 30 Uplighter with adjustable beam angle



LUMINAIRE:

- Die-cast aluminum body and aluminum mounting box
- Stainless steel frame
- Shock resistant tempered glass cover
- Walk over and drive over capacity up to 12 mph

OPTICAL SYSTEM:

- Polycarbonate UV-resistant lenses
- Symmetrical light distribution
- Ultra spot, spot, narrow, medium, flood, wide flood and elliptic optics
- Built-in anti-glare grille for improved visual comfort
- Directional optical system $-5^{\circ} \sim +15^{\circ}$

LIGHT COLOUR MANAGEMENT:

- High uniformity and consistency for facade lighting
- RGBW version available for colour mixing versions

INSTALLATION:

- For outdoor installation with ground recessed mounting box
- Anti-slip glass as optional accessory for improved safety (MOQ)




QUICKINFO

Inground 30W, 4 high-power LEDs
Input DC24V constant voltage
Remote power supply ordered separately
On-board driver available on request (240v)




DIMENSIONS




CODE	Optics	Light colour	Control	Finish colour	Luminous flux
CIG1914W30	spot 5° 0005 spot 8° 0008 narrow 12° 0012 medium 20° 0020 medium 30° 0030 flood 45° 0045 wide flood 60° 0060 elliptic 10°x70° 1070	2700K 2780 3000K 3080 4000K 4080	ON/OFF	stainless steel 01	2,250lm 750lm
*Options CIG1914W30-30W 50 w size reduced to 30w					

Accessories:



honeycomb
for models with optics > 30°



anti-slip glass

Note: MOQ may apply