

Canon 50 Uplighter with adjustable beam angle



LUMINAIRE:

- Die-cast aluminum body and aluminum mounting box
- Stainless steel frame
- Shock resistant tempered glass cover
- Walk over and drive over capacity up to 12 mph

OPTICAL SYSTEM:

- Polycarbonate UV-resistant lenses
- Symmetrical light distribution
- Ultra spot, spot, narrow, medium, flood, wide flood and elliptic optics
- Built-in anti-glare grille for improved visual comfort
- Directional optical system $-5^{\circ} \sim +15^{\circ}$

LIGHT COLOUR MANAGEMENT:

- High uniformity and consistency for facade lighting
- RGBW version available for colour mixing versions

INSTALLATION:

- For outdoor installation with ground recessed mounting box
- Anti-slip glass as optional accessory for improved safety (MOQ)




QUICKINFO

Inground 50W, 6 high-power LEDs
 Input DC24V constant voltage
 Remote power supply ordered separately
 On-board driver available on request (240v)




DIMENSIONS




| CODE | Optics | Light colour | Control | Finish colour | Luminous flux |
|---|------------------------------|--|---------|---------------------------|---------------|
| CIG1914W50 | spot 5° 0005 | 2700K 2780 | ON/OFF | stainless steel 01 | 3,750lm |
| | spot 8° 0008 | 3000K 3080 | | | 2,250lm |
| *Options CIG1914W50-30W 50w Body size reduced to 30w | narrow 12° 0012 | <input type="checkbox"/> 4000K 4080 | | | |
| | medium 20° 0020 | | | | |
| | medium 30° 0030 | | | | |
| | flood 45° 0045 | | | | |
| | wide flood 60° 0060 | | | | |
| | elliptic 10°x70° 1070 | | | | |

Accessories:



honeycomb
for models with optics > 30°



anti-slip glass

Note: MOQ may apply