

Canon 6 Uplighter with adjustable beam angle

LUMINAIRE:

- Stainless steel body with engineering plastic mounting sleeve
- Stainless steel trim
- Shock resistant tempered glass cover
- Walk over and drive over capacity up to 12 mph

OPTICAL SYSTEM:

- Polycarbonate UV-resistant lenses
- Symmetrical light distribution
- Spot, narrow, medium, flood, wide flood and elliptic optics
- Optional anti-glare grille for improved visual comfort
- Directional optical system $-5^{\circ} \sim +15^{\circ}$

LIGHT COLOUR MANAGEMENT:

- High uniformity and consistency for facade lighting

INSTALLATION:

- For outdoor installation with ground recessed mounting sleeve
- Anti-glare grille as optional accessory for improved public comfort (MOQ)
- Anti-slip glass as optional accessory for improved safety (MOQ)




QUICKINFO

Inground 6W, 1 high-power LEDs
 Input voltage 240V constant voltage
 On-board driver



DIMENSIONS



CODE	Optic	Light colour	Control	Finish colour	Luminous flux
CIG1914W10	spot 8° 0008	2700K 2780	ON/OFF	SS 01	480 lm
	narrow 12° 0012	3000K 3080			
	medium 20° 0020	4000K 4080			
	medium 30° 0030				
	flood 45° 0045				
	elliptic 10°x70° 1070				